



PENTEK DFX SERIES DIAMOND FLOW CARTRIDGES

DUAL-TECHNOLOGY FILTRATION



DFX Series Diamond Flow cartridges are a unique, premium cartridge that utilizes several of the Pentair core competencies by merging technologies into one cartridge in order to bring customers a quality product. Diamond Flow Series cartridges offer the effective chlorine taste & odor reduction found in traditional Pentek[®] carbon blocks, joined with the superior sediment reduction to resist premature plugging. These dual purpose cartridges are well-suited for a wide range of applications.

FEATURES/BENEFITS

High dirt-holding capacity maximizes utilization of the carbon block*

Chlorine taste & odor reduction combined with superior sediment reduction*

Available in a 10-micron rating

Available in 10" & 20" lengths

Available in Standard & Big Blue[®] Size

Low pressure drop

New product design with Pentair branding

Twice as resistant to particulate plugging than standard carbon blocks*

MATERIALS OF CONSTRUCTION

Exterior Filter Media:
Polypropylene Polyspun

Interior Filter Media:
Carbon Block

Endcaps: Polypropylene

Gaskets: Buna-N

Temperature Rating: 40°-125°F

*Based on manufacturer's internal testing.

SPECIFICATIONS AND PERFORMANCE

PART NUMBER	MODEL	MAXIMUM DIMENSIONS	RATING (NOMINAL)	INITIAL ΔP (PSI) @ FLOW RATE (GPM)	CHLORINE TASTE & ODOR REDUCTION @ FLOW RATE
655130-43	DFX-CB-10	2.89" x 9.81" (73.406 mm x 249.174 mm)	10 μ	1.0 psi @ 1.0 gpm (0.07 bar @ 3.8 Lpm)	2,500 gal @ 1.0 gpm (9,464 L @ 3.8 Lpm)
655148-43	DFX-CB-20	2.89" x 20.035" (73.406 mm x 508.89 mm)	10 μ	1.0 psi @ 2.0 gpm (0.07 bar @ 7.6 Lpm)	5,000 gal @ 2.0 gpm (18,927 L @ 7.6 Lpm)
655151-43	DFX-CB-BB	4.63" x 9.81" (117.60 mm x 249.174 mm)	10 μ	1.0 psi @ 2.0 gpm (0.07 bar @ 7.6 Lpm)	15,000 gal @ 2.0 gpm (56,781 L @ 7.6 Lpm)
655152-43	DFX-CB-20BB	4.63" x 20.035" (117.60 mm x 508.89 mm)	10μ	1.0psi @ 4.0 gpm (0.07 bar @ 15.14 Lpm)	30,000 gal @ 4.0 gpm (113,562 L @ 15.14 Lpm)